DRIFT THICKNESS OF CRYSTAL LAKE QUADRANGLE

Department of Natural Resources ILLINOIS STATE GEOLOGICAL SURVEY William W. Shilts, Chief



B. Brandon Curry 2005

Illinois Geologic Quadrangle Map IGQ Crystal Lake-DT

HARVARD 20 MI. 10 HENRY 17/30/ 176 MUNDELEIN 16 MI. WAUCONDA 8 MI 88°22'30" R7E R8E 393 CRYSTAL LAKE LakeKillarney Crystal Vista CrystalLake 12'30" 12'30" AKE IN THE

Introduction

This map provides an estimate of the glacial drift thickness in the Crystal Lake 7.5minute Quadrangle. Mapping the thickness of this material provides basic information for land use, planning, and economic development decisions.

Drift refers to geologic materials from various sedimentary environments that resulted directly or indirectly from continental glaciation. Drift includes till, sand and gravel outwash, lake sediment, loess (wind-blown silt), alluvium, peat, and debris flows. It also includes deposits from mass movement, such as landslides or down-slope soil creep. Drift is important for two reasons: the fine-grained materials offer some measure of protection from surface contaminants for underlying bedrock aquifers, and drift is an important economic factor in the development of bedrock quarries. To assess bedrock aquifer vulnerability fully, however, additional information such as the porosity and permeability of the sediment constituting the non-aquifer and aquifer materials are necessary. As available sand and gravel aggregate resources become depleted in northeastern Illinois, aggregate companies have increasingly become interested in developing underground bedrock aggregate mines, such as the currently operating Conco-Western Quarry in North Aurora. The expense of developing underground mines increases with thicker drift.

Methods

This drift thickness map was produced with the computer program Vertical Mapper 2.0 using the nearest neighbor algorithm. A 100-meter (328-foot) grid of drift thickness values was determined by subtracting the elevation value grid of the bedrock topography from that of the ground surface. The gridded values of ground surface elevations have an accuracy of \pm 5 feet (USGS 1999). Figure 1 is a shaded relief map of the 10-meter digital elevation model of the ground surface. Values of drift thickness were calculated from 342 water wells and 8 stratigraphic borings. These data are available from the Illinois State Geological Survey Geological Records Unit and are identified on a 1:24,000-scale map (Curry 2005a). Both the bedrock surface contours of Curry (2005b) and drift thickness data points were used in the gridded model of the bedrock surface topography.





MILES

Figure 1 Shaded relief map of the Crystal Lake Quadrangle using the 10-meter USGS digital elevation model of the quadrangle. The Woodstock and Barlina Moraines are shaded green (modified from Hansel and Johnson 1989, Willman and Frye 1970). Scale is 1:100,000.

Discussion

Drift thickness in the Crystal Lake Quadrangle varies from about 25 feet to more that 275 feet. Because the bedrock surface has half the relief of the surface topography (100 feet vs. 200 feet), patterns of drift thickness are more of a reflection of the surface topography. Low-lying areas, such as the valley of the Fox River and its tributaries, are underlain by thinner drift. The Woodstock Moraine (Hansel and Johnson 1989) and Barlina Moraine (Willman and Frye 1970) (fig. 1) are underlain by thicker drift. The Woodstock Moraine is an end moraine formed of thick sand and gravel overlain by relatively thin, loamy, poorly sorted sediment (diamicton) (Curry 2005c). The Barlina Moraine is formed by thin deposits of diamicton and sorted sediment associated with the Yorkville and Batestown Members (Lemont Formation) draped over a thick succession of diamicton of the Tiskilwa Formation (Curry 2005c). The irregular edges of the moraines, especially the Barlina Moraine, are attributed to postglacial erosion by the Fox River and its tributaries.

References

- Curry, B.B., 2005a, Data point locations of Crystal Lake Quadrangle, McHenry and Kane Counties, Illinois: Illinois State Geological Survey, Illinois Geological Quadrangle Map, IGQ Crystal Lake-DP, 1:24,000.
- Curry, B.B., 2005b, Bedrock topography of Crystal Lake Quadrangle, McHenry and Kane Counties, Illinois: Illinois State Geological Survey, Illinois Geological Quadrangle Map, IGQ Crystal Lake-BT, 1:24,000.
- Curry, B.B., 2005c, Surficial geology of Crystal Lake Quadrangle, McHenry and Kane Counties, Illinois: Illinois State Geological Survey, Illinois Geological Quadrangle Map, IGQ Crystal Lake-SG, 1:24,000.
- Hansel, A.K., and W.H. Johnson, 1989, Age, stratigraphic position, and significance of the Lemont Drift, northeastern Illinois: Journal of Geology, v. 97, p. 301-318.
- United States Geological Survey, 1999, Map accuracy standards, Fact Sheet FS-171-99: http://mac.usgs.gov/mac/isb/pubs/factsheets/fs17199.html.
- Willman, H.B., and J.C. Frye, 1970, Pleistocene stratigraphy of Illinois: Illinois State Geological Survey, Bulletin 94, 204 p.

Drift Thickness

Base map compiled by Illinois State Geological Survey from digital data provided by the United States Geological Survey. PLSS compiled in 1991. Hypsography compiled 1992. Transportation and hydrography updated from imagery dated 1999.

North American Datum of 1983 (NAD 83) Projection: Transverse Mercator 10,000-foot ticks: Illinois State Plane Coordinate system, east zone (Transverse Mercator) 1,000-meter grid: Universal Transverse Mercator grid, zone 16

Recommended citation:

Curry, B.B., 2005, Drift Thickness of Crystal Lake Quadrangle, McHenry and Kane Counties, Illinois: Illinois State Geological Survey, Illinois Geologic Quadrangle Map, IGQ Crystal Lake-DT, 1:24,000.

SCALE 1:24 000										
1	1/2		0						1 MILE	
	1000	0	1000	2000	3000	4000	5000	6000	7000 FEET	
					1 KILOMETER					

BASE MAP CONTOUR INTERVAL 10 FEET NATIONAL GEODETIC VERTICAL DATUM OF 1929

Released by the authority of the State of Illinois: 2005

Geology based on field work by B. Curry, 1998–2001.

Digital cartography by M. Barrett and J. Domier, Illinois State Geological Survey.

The Illinois State Geological Survey, the Illinois Department of Natural Resources, and the State of Illinois make no guarantee, expressed or implied, regarding the correctness of the interpretations presented in this document and accept no liability for the consequences of decisions made by others on the basis of the information presented here. The geologic interpretations are based on data that may vary with respect to accuracy of geographic location, the type and quantity of data available at each location, and the scientific and technical qualifications of the data sources. Maps or cross sections in this document are not meant to be enlarged.



Data Type

- Stratigraphic boring \bullet
- Water well
- Engineering boring
- SG Boring with samples (s) or geophysical log (G); dot indicates to bedrock

Note: Numeric labels indicate drift thickness in feet.



Champaign, Illinois 61820-6964 (217) 244-2414 http://www.isgs.uiuc.edu





